

AutoFlush[®] Tank

Touch-Free Tank Toilet Flushing System



technical concepts
Innovative Hygiene Solutions



- Keeps Toilets Flushed and Presentable
- Unique Wireless Sensor Enables Easy Installation
- Ultra-Compact
- World-Class Reliability

AutoFlush® Tank

The AutoFlush® Tank ensures that toilets are always flushed and presentable. This wireless system promotes good hygiene by eliminating potential points of cross-contamination while preventing odors due to unflushed fixtures.

Keeps Toilet Flushed and Presentable

Ensures that tank toilets are always flushed and presentable. No trailing costs for replacement parts, simply change batteries every 100,000 cycles or 3 years.

World-Class Reliability

Smart Object Infrared Technology manages flushing automation like no other system. The wireless sensor located directly behind the washroom patron guarantees activation even if the toilet seat is raised. This dependable technology ensures good hygiene for patrons and occupants of your facilities.

Ultra Compact and ADA Compliant

The compact motor fits most tank styles and displaces little water. No need to replace your current investment of tank type toilets or move plumbing hardware to accommodate ADA compliance.

Easy Wireless Installation

Installing the AutoFlush® Tank is an easy and cost effective way to gain the benefits of an automated flushing system. Simply mount the motor in the tank, install sensor and insert batteries.


Easy 1,2,3 Step Installation



Mount Motor in Tank



Install Sensor



Insert Batteries

AutoFlush® Tank Features:

- IR Receiver
- Green Object Detection Indicator
- Wave Range Adjustment Dial
- Mode Toggle
- Object Detection Range Adjustment Dial
- Reset
- 24 Hr Flush (on)
- Yellow Battery Power Indicator
- IR Emitter



The AutoFlush® Tank comes with three modes of operation:

- A) Object Detection** - toilet will flush 5 seconds after patron has left the sensing zone (32" factory setting). For immediate flush, the patron can wave their hand in front of the sensor. **This is the factory setting.**
- B) Object Detection with Extended Delay** - toilet will flush 7 seconds after patron has left the sensing zone (32" factory setting). For an immediate flush the patron can wave their hand in front of sensor.
- C) Wave Only** - toilet will flush only when the patron has waved their hand in front of the sensor.

AutoFlush® Tanks:



750831

AutoFlush® for Tank Toilets:

Stock#	Description
750831 AutoFlush for Tank Toilets Wireless (white)



ADA COMPLIANT



technical concepts
Innovative Hygiene Solutions

World Headquarters:
Serving North and South America

Technical Concepts LLC
1301 Allanson Road
Mundelein, Illinois 60060 U.S.A.
Toll Free: 1-800-551-5155
Fax: 1-800-551-5046

www.technicalconcepts.com

European Headquarters:
Serving Europe, Africa and Middle East

Technical Concepts International Ltd.
Peterborough, PE2 6WA, England
Phone: +44 (0)870 568 6824

Asian Headquarters:
Serving Asia and Pacific

Technical Concepts Asia
14100, Penang, Malaysia
Phone: (60) 4 508 5008

